
## **Scale Pallet Truck**





- The instrument operation interface is concise and easy to operate.
- The display screen is 6-digit LCD display, and the screen is inclined forward, which is convenient for the operator to read the value.
- The maximum error value of the instrument is 0.1%, and the weighing accuracy is 0.5kg.
- Five functional buttons, easy and simple to operate.
- It can switch the weighing unit (kg / lb) with one key, which is convenient for use in different markets requirements.
- The instrument power supply adopts 4.8V/4AH lithium battery, which can be used continuously for more than 60 hours, stand-by for up to 300 hours, and charging only takes 5 hours.
- The instrument screen is equipped with backlight, which will automatically light up when the weight changes, which is convenient
  for the operator to check; after the weight is stable, the backlight will automatically turn off for saving energy.
- The back of the instrument is totally enclosed, and the harness connection adopts aviation connector / RS232 connector, which
  improves the overall protection performance of the instrument.
- The whole instrument is protected by iron plate, which prevents the instrument from bumping and damage during operation.
- Optional thermal printer, with no need to change the color band.



		1KG=2.205LB	1INCH=25.40MM
Model	BFC6-7E/BFC6-8E		
Capacity	(kg)	2000	
Lowered fork height	(mm)	76/85	
Total lift height	(mm)	165/175	
Fork length	(mm)	1150	
Width fork overall	(mm)	540/570/705	
Steering wheel	(mm)	ф 160	
Fork wheel	(mm)	ф70	
Power		4.8V/4Ah li-ion battery	
Max. deviation(weight)	(kg)	0.5	
Max.deviation(rate)	(%)	±0.1%	
Turning radius	(mm)	1368	
Service weight	(kg)	115-130	